

COVERPRO[®] SA

SYNTHETIC ROOFING UNDERLAYMENT

Self-Adhered Roof Underlayment



PRODUCT OVERVIEW

CoverPRO[®] SA is the new evolution of ice damming and wind-driven rain protection. It combines all the features and benefits you expect from a high-temperature rubberized asphalt adhesive product, and adds a new, dynamic synthetic walking surface.

Our revolutionary, non-woven walking surface is manufactured from 100% synthetic materials. A split release film protects the adhesive and is removed as the underlayment is installed.

CoverPRO SA is high-temperature rated and approved for commercial and residential applications, meeting or exceeding code requirements for nail sealability testing. In addition, CoverPRO SA is approved for use under all primary roofing materials, including steel, tile, slate and asphalt shingles.

CoverPRO SA is durable and dependable, allowing you to leave it exposed for up to 90 days.

FEATURES

VERSATILE: CoverPRO SA can be installed within 40°F to 240°F, giving contractors the versatility for a wide range of projects.

EASIER: CoverPRO SA installs quickly and easily. A split release liner and a lighter weight material (20% lighter than traditional sanded self-adhered underlayment) save time and money on the job site.

SAFER: Proprietary CoverPRO SA walking surface offers an industry leading steep-slope traction, improving roof deck walkability in all conditions.

FLEXIBLE: CoverPRO SA is specifically designed to withstand harsh effects from cold temperatures, preventing the product from becoming stiff or brittle.

TOUGHER: CoverPRO SA is substantially stronger than similar products offered in the market. It is resistant to delamination, stretching and tearing. It is also engineered to resist excessive degradation from normal UV exposure for up to 90 days.

CODE COMPLIANT: CoverPRO SA is designed to meet both residential and commercial roofing building codes.

WARRANTY: CoverPRO SA is backed by a 10-year limited warranty.

Property	Standard	Unit of Measurement	CoverPRO SA Typical Result ¹
Thickness	D5147	mils (0.001")	44
Tensile Strength (MD/CD)	D1970	lbf/inch	58/54
Thermal Stability	D1970	n/a	Pass
Cold Temperature Flexibility	D1970	n/a	Pass
Moisture Vapor Permeability	E96, Method A	perms	0.067
Nail Sealability	D1970	n/a	Pass
Maximum Outdoor Exposure	n/a	days	90

¹Results reflect typical properties of control/non-conditioned specimens. Values should not be interpreted as limiting specifications and will vary within typical manufacturing tolerances.

COVERPRO SA PACKAGE SPECIFICATIONS

- Roll Dimensions 36" x 67'
- Weight per Roll 55 lbs
- Coverage per Roll 201 sq ft (gross)
- Rolls per Pallet 30
- Pallet Weight 1650 lbs

CODE & STANDARD COMPLIANCE

- ASTM D1970 TYPE II
- CSA A 123.22
- FBC# FL25578
- QAI B1040-2



COVERPRO[®] SA
SYNTHETIC ROOFING UNDERLAYMENT

Phone: 330-528-0255
Email: support@systemcomponents.net
Web: systemcomponents.net

System Components Corporation
10 West Streetsboro Street, #207
Hudson, OH 44236

CoverPro is a registered trademark of System Components Corporation.
© 2018 System Components Corporation. All rights reserved.

CoverPRO SA - PRODUCT INFO 201811

1 of 1